



1155-10

ST _ LPS_ CR _10 526

INVESTIGATION OF COSMIC RADIATION ON

THE AMS "LUNA-10"

ъу

N. L. Grigorov V. L. Maduyev N. F.. Pisarenko I. A. Savenko

(USSR)

N 67 12238	(THRU)	GPO PRICE \$
(NASA CR OR TMX OR AD NUMBER)	CATEGORY	Hard copy (HC)
(<u> </u>	•	Microfiche (MF)
		ff 653 July 65

25 OCTOBER 1966

INVESTIGATION OF COSMIC RADIATION ON

THE AMS "LUNA-10"

Doklady A.N. SSSR, Geofizika Tom 170, No. 3, 565-6, Izadtel'stvo "NAUKA", 1966 by N. L. Grigorov V. L. Maduyev N. F. Pisarenko I. A. Savenko

$\underline{S\ U\ M\ M\ A\ R\ Y}$

12238

On the basis of observations from the AMS Luna-10, the magnitude of the flux of primary cosmic radiation remains fairly high in spite of solar activity rise begun in 1966, maintaining a value characteristic for solar activity minimum. These data agree well with those obtained two months earlier with the aid of another type of spacecraft — LUNA-9.

* Author

Two end-window gas-dicharge counters, located in sequence in the upper part of satellite's cone, were part of the instrumentation aboard LUNA.10 designed to investigate the cosmic radiation by means of the first satellite of the Moon. The axes of the counters were oriented parallelwise to the axis of the satellite. In order to separate cosmic radiation by hardness, the counter had different shielding. The one designed to register the hard cosmic radiation (of galactic cosmic rays, and of cosmic rays of solar origin) was closed from all sides by a copper screen of 2.5 g cm⁻² thickness. Protons with energies greater than 50 Mev and electrons with energies greater than 5 Mev, could penetrate through such a shielding. The indicated particles were registered with efficiency near the unity. The counter destined to register the feebly-penetrating cosmic radiation, with solid angle near 10 ster was closed by exactly the same shielding, but from the end it had a thin window made of 1.2 milligrams of mica \pm 0.3 mg gold per 1 cm 2 . The width was 0.5 cm in diameter, the solid viewing angle had near 2 ster. Protons with energies greater than 0.5 Mev and electrons with energies greater than 40 kev could pass through the window.

The global geometric factor of each of the counters for the isotropic hard radiation constitutes 2.6 ± 0.2 cm. The counter registering the feebly-penetrating radiation had a geometrical factor of 0.4 ± 0.1 cm ster. The counters were fed from the general voltage transformer. The counting rate was measured with the aid of logarithmic discrete count circuits. The mantissa and the characteristic number of pulses, registered by each counter, were transmitted to the Earth every two minutes during sessions. During the first cycle of a session data on the number of pulses computed during the previous seesion were transmitted to Earth. The precision of transmission of numbers, determined by the accuracy of transmission of mantissa, was always better than 3 percent. The capacity of the logarithmic circuit constituted $5 \cdot 10^8$ pulses. The information received covered the period from 31 March to 29 May.

^{*} Issledovaniye kosmicheskogo izlucheniya na iskusstvennom sputnike Luna-10.

Observations of the integral level of cosmic radiation in free interplanetary space were conducted in the period from 31 March to 3 April 1966. We dispose of data for three sessions, of 30 minutes duration each. The mean rate of hard electrons' counting by the shielded counter constituted 12.2 ±0.1 sec-1. which corresponds to a flux of 4.7 ± 0.4 cm⁻² sec⁻¹.

The value of the flux of primary cosmic radiation is evidence that despite the already increased solar acticity, having begun to rise in 1966, the intensity of primary cosmic radiation continues to maintain a sufficiently high value characteristic of for the period of solar activity minimum. The value of the flux, as brought out here, coincides with the data obtained two months earlier with the help of a counter installed on board of Luna.9. quite different in its type. Refer to [1].

The satellite LUNA-10 entered a selenocentrical orbit on 3 April 1966, with aposelion at 1000 km, periselion at 350 km, and an inclination angle to the axis of rotation of the Moon, 72°. A depedence was obtained of the counting rate of the shielded counter on height above the surface of the Moon. This dependence is shown in Fig. 1.

pulse/sec rate 11 counting 108 9 L

800 600 #1titude above the surface of the Moon

The experimentally measured variation of the counting rate of the shielded counter between aposelion and periselion constitutes $11 \pm 3^{\circ}$. The shielding by the Moon for an albedo equal to zero must give a variation near 15 percent.

Contribution to the counting rate of the nonshielded counter was made by feeblypenetrating cosmic rays of solar origin

and the soft radiation in the region of the assumed boundary of the Earth's magnetosphere tail (see the immediately following paper by N. L. Grigorov, B. L. Maduyev, t al ST - PF - LPS - 10 528)

> END totak THE ماله مالومول مراد

Institute of Physics in the name of P. N. Lebedev of the USSR Ac. of Sc. Received on 4 July 1966

Contract No.NAS-5-12487 VOLT TECHNICAL CORPORATION 1145 19th st. Washington D.C. 20036. Tel:223-6700 Translated by ANDRE L. BRICHANT

on 25 October 1966

REFERENCE

1. S. N. VERNOV, P. V. VAKULOV ET AL. Dok1.AN.SSSR, 169, 5, 1966.

LNH VOLT

DISTRIBUTION

GODE	DARD SPACE F.C.	<u>N</u>	ASA HQS	OTHER CENTERS
100,	110, 400, 601	SS	NEWELL, NAUGLE	AMES R C
610	MEREDITH	SG	MITCHELL, SMITH	
611	McDONALD (11)		SCHARDT	SONETT (3)
612	HEPPNER (6)		GAUGLER	LIBRARY
613	KUPPERIAN (6)		DUBIN	
614	WHITE (4)		ROMAN	LANGLEY R C
615	BAUER	SL	WILMARTH	
	GOLDBERG, HERMAN		BRYSON	116 KATZOFF
	MAIER		MOLLOY	160 ADAMSON
	STONE		FELLOWS	185 WEATHERWAX (2)
640	HESS		HIPSHER	
	O'KEEFE		HOROWITZ	JET PROP.LAB.
641	MEAD, MAEDA	SM	FOSTER	
	NORTHROP		GILL	T-122 LPS (3)
	NAKADA	RR	KURZWEG	186-133 SpSc (3)
	JONES	RTR	NEILL	VIS-LAB WYCKOFF
	BURLEY, KELSALL	WX	SWEET	111-113 LIBRARY
	READING RM	USS	NAGURNIY	
630	GI for SS (5)			+ all perm. addressees
620	SPENCER			
2 52	LIBRARY			
256	FREAS			